Four 12G-SFP input card for LivePremier™ series Ref. ACC-AQL-IN-SFP



Field swappable input card for LivePremier™ series with four 12G-SFP ports



4K60 4:4:4

12G-SDI

HDR

HFR up to 120Hz

Overview

The Analog Way ACC-AQL-IN-SFP is a field swappable input card with four 12G-SFP ports, designed to work with any LivePremier™ live presentation switcher. Each input port is compatible with video non-MSA SFP receiver modules and supports resolutions up to 4K60 10bit 4:2:2. The card supports up to 8 embedded audio channels per input.

Key features

- ► Four 12G-SFP seamless input ports
- ► Compatible with any standard non-MSA (video) SFP receiver modules (coax, fiber, HDMI, IP...)
- ► Field swappable card (not hot swappable)
- ► True 4K60 4:2:2 performance on every input port
- ► Supports 4K60 input as single, double or quad ports
- ► Connector status LEDs for easy troubleshooting
- ► HDR compliant with HDR10 and HLG
- ► High Frame Rate up to 120Hz

Technical Specifications

Four 12G-SFP input ports

Up to 12Gbps bandwidth per port

10-bit formats up to:

- 4K60 4:2:2
- 4K30 4:4:4

Compatible with SD-SDI, HD-SDI, 3G-SDI (Level A and B) and 6G-SDI

Supports BT.709 and BT.2020 color spaces

Dimensions

- ► W 5.10" x H 1.66" x D 5.80"
- L 129.7 mm x H 42.3 mm x P 147.4 mm

Weight without accessories

▶ 0.26 kg / 0.57 lbs

Shipping weight accessories included

▶ 0.45kg / 0.99 lbs

Operating conditions

- ► Temperature: 0 to 40°C (32 to 104°F)
- ► Humidity: 10% to 80%, non-condensing

Warranty

- ▶ 1-year warranty on parts and labor back to factory
- ▶ Broken connectors are not covered by warranty

Power supply

▶ Powered from LivePremier™ switcher

Safety Compliance

- ► IEC/UL/EN 62368-1
- ► CSA22.2#62368-1
- ▶ (UL Listed E359143)

Specifications subject to change without prior notice

ACC-AQL-IN-SFP-EN-26/08/2021





